

25081 Overall

Suggested fabrics:

Light weight fabric

Cut:

1. Back pants - X2
2. Front pants - X2
3. Center back - X2
4. Side back - X2
5. Side front - X2
6. Center front - X2
7. Back facing - X4
8. Front facing - X2
9. Back armhole facing - X2
10. Front armhole facing - X2
11. Back side facing - X2
12. Front side facing - X2

Seam allowances:

All seams 1 cm (3/8"). Pants hem 3 cm (1 1/8");

Sewing instruction:

1. Stitch side back panels to centre back.
2. Stitch side front panels to centre front.
3. Stitch seams on side facings.
4. Stitch side facing to side seams (making a hole); fold in and topstitch.
5. Stitch about 10 cm on centre front; from waistline keeping wide seam allowance. Fold in and press seam allowance.
6. Stitch side seams on armhole facings.
7. Stitch armhole facing to armhole. Fold in and topstitch.
8. Prepare and stitch neck facing into neck line. Place two hooks on centre back of the facing.
9. Stitch side seams on pants.
10. Stitch inseam on pants.
11. Stitch crotch seam. Leave about 16 cm from back side to zipper.
12. Stitch top to pants on waistline.
13. Insert zipper into centre back pants.
14. Fold in and topstitch pants hem.